



















TAB. B COMPENSATED CONNECTORS

Compensated connectors and accessories – colour marking according to IEC. Available for sensor types J, K, N, E, T, R/S, B and RTD.

STANDARD CONNECTORS		MINIATURE CONNECTORS	
 <p>SG1 SW1</p>	<p>plug: SW1 jack: SG1 temperature rating: 200 °C max. eg. plug SW1-K or jack: SG1-K</p>	 <p>MG1 MW1</p>	<p>plug: MW1 jack: MG1 temperature rating: 200 °C max. eg plug MW1-K or jack MG1-K</p>
No standard version		 <p>MW6 MG6</p>	<p>Connector with protection against accidental disconnection plug: MW6 jack: MG6 temperature rating: 200 °C max. eg. plug MW6-K or jack MG6-K plug and jacket suit to MW1 i MG1</p>
 <p>SG10 SW10</p>	<p>For high temp. plug: SW10 jack: SG10 temperature rating: 350 °C max. eg. plug SW10-J or jack: SG10-J</p>	 <p>MG10 MW10</p>	<p>For high temp. wtyk: MW10 jack: MG10 temperature rating: 350 °C max. eg. plug MW10-J or jack MG10-J</p>
 <p>SG100 SW100</p>	<p>Ceramic plug: SW100 jack: SG100 temperature rating: 650 °C max. eg. plug SW100-S or jack: SG100-S</p>	 <p>MG100 MW100</p>	<p>Ceramic plug: MW100 jack: MG100 temperature rating: 650 °C max. eg plug: Mw100-R or jacket MG1000-R</p>
 <p>SG2 SW2</p>	<p>With the additional ground pin plug: SW2 jack: SG2 temperature rating: 200 °C max. for 3-wire RTD sensors or grounded thermocouples</p>	 <p>MG2 MW2</p>	<p>With the additional ground pin plug: MW2 jack: MG2 max. temp. pracy: 200 °C temperature rating: 200 °C max. for 3-wire RTD sensors or grounded thermocouples</p>
 <p>SG3 SW3</p>	<p>Duplex plug: SW3 jack: SG3 temperature rating: 200 °C max. for two-circuit thermocouple or 4-wire RTD-'s.</p>	 <p>MG3 MW3</p>	<p>Duplex plug: MW3 jack: MG3 temperature rating: 200 °C max. for two-circuit thermocouple or 4-wire RTD-'s.</p>
 <p>SG4</p>	<p>jack: SG4 temperature rating: 200 °C max.</p>	 <p>MG4</p>	<p>jack: MG4 temperature rating: 200 °C max.</p>
 <p>SG5</p>	<p>Entrance hole Ø27 mm jack: SG5 temperature rating: 200 °C max.</p>	 <p>MG5</p>	<p>Entrance hole Ø17,5mm jack: MG5 temperature rating: 200 °C max</p>
 <p>SG7</p>	<p>Multiple pin jack, 3 thermocouple and RTD circuit jack: SG7 temperature rating: 200 °C max. *) in thermocouples: the 3rd circuit is, e.g. for screen connection</p>	 <p>MG7</p>	<p>Multiple pin jack, 3 thermocouple and RTD circuit jack: MG7 temperature rating: 200 °C max. *) in thermocouples: the 3rd circuit is, e.g. for screen connection</p>
No standard version		 <p>MG8</p>	<p>Panel jack for a plug type MW6 jack: MG8 temperature rating: 200 °C max.</p>

Ordering code: eg. SW1 - K or MWL - J etc.